



Visco 3000 10W-40
Cleanguard Engine Protection Technology

Applications

BP Visco 3000 10W-40 with Cleanguard Engine Protection Technology is a part synthetic engine oil suitable for use in automotive gasoline and diesel engines where the manufacturer recommends API SL/CF or ACEA A3/B3 or earlier specifications.
Visco 3000 10W-40 is also approved for use in VW and Mercedes cars that require VW505 00 or MB 229.1 specification oils.

Features / Benefits

BP Visco with Cleanguard Engine Technology keeps your engine cleaner for longer.

BP Visco 3000 10W-40 is a premium part synthetic engine oil that provides:

- Improved engine cleanliness
 - Advanced protection for normal driving conditions
 - Reduced oil consumption
-

Specifications / Performance

API SL/CF
ACEA A3/B3

MB-Approval 229.1
VW 505 00

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products.

Castrol (UK) Ltd. or its subsidiaries will not accept liability if the product is used other than in the manner or with the precautions or for the purpose/s specified. Before the product is used other than as directed, advice should be obtained from the local Castrol office.

Typical Characteristics

Test Methods

Units

Value:

SAE 10W-40

<i>Test</i>	<i>Method(s)</i>	<i>Unit</i>	<i>Typical</i>
Density @ 15C, Relative	ASTM D4052	g/ml	0.873
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	14.2
Viscosity, CCS -25C (10W)	ASTM D5293	cP	5880
Calcium, % wt	ASTM D4951	% wt	0.226
Phosphorus, % wt	ASTM D4951	% wt	0.093
Zinc, % wt	ASTM D4951	% wt	0.103
Viscosity, Kinematic 40°C cSt	ASTM D445	cSt	95
Viscosity Index	ASTM D2270	None	154
Pour Point	ASTM D97	°C	-36
Ash, Sulphated	ASTM D874	% wt	1.05
Total Base Number, TBN	ASTM D2896	mg KOH/g	8
Flash Point, PMCC	ASTM D93	°C	189

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

This Data sheet and information it contains is considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication.

It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence.

The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).

Castrol UK Ltd, Wakefield House, Pipers Way, SWINDON, Wiltshire. SN3 1RE
www.castrol.com/uk
Telephone: 01793 512712
Automotive Technical Helpline: 01793 452222
Orders/Enquiries: 0845 6008125 (Workshop Customer Order Line) 0845 6008131 (Retail Customer Order Line)

Castrol Ireland, Suit 12, Plaza 212, Blanchardstown Business Park Phase 2, Blanchardstown, DUBLIN 15, Ireland www.castrol.com/ie
Automotive Technical Helpline: 1800 509 353
Orders/Enquiries: 01 866 5100
29/04/2010

Date Created: 22/02/2008 13:26:04 Last Modified: 29/04/2010